

H.264 DVR KPD678

16 CH H.264 Real Time Recording Network DVR



Features

- **VGA Support**
VGA interface built-in
Output resolution support up to 1600 x 1200
- **Fully Remote Independent Operation**
The operation between the local site and remote site won't affect each other.
The remote operation is fully independent
- **Saving HDD Capacity**
Allows single-channel recording when a motion alarm is triggered
- **H.264 Technology**
H.264 compression format providing crystal clear images with real time performance
H.264 web transmitting for faster transmission and clear images via network
- **Multiplex**
Allows live display, record, playback, backup and network operation at the same time
- **Free Upgrade to Advanced Functions**
Allows you to upgrade DVR functions without any charges
- **Backup Function**
Supports USB flash drive and network backup
- **Remote Surveillance**
Supports remote surveillance up to 5 users simultaneously via the licensed software "Video Viewer", Internet Explorer or Mozilla Firefox web browser, and QuickTime player
- **Intelligent Motion Trigger Recording**
R.E.T.R. (Remote Event Trigger Recording)
Activates event recording automatically when alarm is triggered, and send a URL link for image download to designated e-mails/FTP address
Customizable security settings are achieved with the advanced motion detection, the scheduled motion detection recording (with 1 adjustable parameter), and the quick search function
Supports pre-alarm recording (8MB)
- **Audio Support**
Supports 4 audio-in, 1 audio-out to record sounds
- **Cover Recording**
Blank screen replaces live displays to achieve covert recording
- **General**
 - * Supports multi-language OSD
 - * Supports SATA HDDs (SATA interface built-in)
 - * Supports IR remote control
 - * Supports remote control and live view via Ethernet
 - * System auto recovery after power failure
 - * Supports manual/timer/motion/alarm/remote recording
 - * Supports TCP/IP, PPPoE, DHCP and DDNS network connection

Specification

MODEL	KPD678
Video System	NTSC / PAL (auto detection)
Video Compression Format	H.264
Video Input	16 channels (composite video signal 1 Vp-p 75Ω BNC)
Video Output	Main monitor output (composite video signal 1 Vp-p 75Ω BNC)
Audio Input/Output	4 audio inputs, 1 audio output (Mono)
Maximum Recording Rate (Frame)	704×480 pixels with 60 IPS <NTSC> / 704×576 pixels with 50 IPS <PAL>
Maximum Recording Rate (Field)	704×240 pixels with 120 IPS <NTSC> / 704×288 pixels with 100 IPS <PAL>
Maximum Recording Rate (CIF)	352×240 pixels with 240 IPS <NTSC> / 352×288 pixels with 200 IPS <PAL>
Adjustable Recording Speed (Frame)	120, 60, 30, 15 IPS <NTSC> / 100, 50, 25, 12 IPS <PAL>
Adjustable Recording Speed (Field)	240, 120, 60, 30 IPS <NTSC> / 200, 100, 50, 25 IPS <PAL>
Adjustable Recording Speed (CIF)	480, 240, 120, 60 IPS <NTSC> / 400, 200, 100, 50 IPS <PAL>
Multilingual OSD	YES
Image Quality Setting	Best, High, Normal and Basic
Hard Disk Storage	Accommodates 2 SATA HDDs (1 HDD capacity up to 1TB)
SATA Interface	Built-in
VGA Interface	Built-in (output resolution up to 1600 x 1200)
Quick Search	Time / Motion / Alarm search mode
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Refresh Rate	480 IPS for NTSC / 400 IPS for PAL
Multiplex Operation	Live display / record (16 channels) / playback (simultaneously up to 4 channels) / backup / network operations
Independent Remote Operation	Fully remote independent operation
R.E.T.R. (Remote Event Trigger Recording)	YES
Motion Detection Area	16 × 12 grids per camera for all channels
Motion Detection Sensitivity	One parameter with three sensitivity levels (High / Normal / Low)
Pre-alarm Recording	YES (8 MB)

PRODUCT SPECIFICATION

Backup Device	USB 2.0 flash drive / Network
USB Interface	Front panel * 1 / Back panel * 1
Web Transmitting Compression Format	H.264
Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Web Interface	Licensed software "Video Viewer" / Internet Explorer or Mozilla Firefox web browser / QuickTime player (5 users access simultaneously)
	*Operating System: Windows Vista / XP / 2000; Apple Mac
	TCP/IP, PPPOE, DHCP and DDNS
Network Independent	YES (IR receiver built-in)
IR Remote Control	YES
PTZ Control	Programmable with adjustable dwell time (3 / 5 / 10 / 15 seconds)
Dwell Time (Sequential Channel Switch)	16 inputs, 1 output
Alarm Input / Output	2X digital zoom (Live & Playback)
Picture Zoom	YES
Key Lock (Password Protection)	YES
Video Loss Detection	YES
Camera Title	Supports up to 6 letters
Video Adjustable	Hue / Saturation / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off
Daylight Saving	YES
Power Source ($\pm 10\%$)	DC 19V
Power Consumption ($\pm 10\%$)	< 64 W
Operating Temperature	10? ~ 40? (50?~104?)
Dimensions (mm)**	430(W) x 65(H) x 338(D)
System Recovery	System auto recovery after power failure
Optional Peripherals	Keyboard controller

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5 mm